

Amendments to the Claims

A complete listing of the claims follows:

1. (Currently amended) A networked imaging system, comprising:

a first communications network;

a second communications network, different than the first communications network;

a first storage device interconnected to the first network;

a second storage device interconnected to the second network;

a first raster image processor interconnected to the first network and the second network, and configured to generate first image data representing a first image and to write the first image data to the first storage device via the first network, and to transmit via the second communications network a message indicative of the first image data having been written to the first storage device;

a second raster image processor interconnected to the second network, and configured to generate second image data representing a second image and to transmit the second image data over the second network;

a first print driver server interconnected to the first and the second networks, and configured to receive the second image data over the second network and to write the second image data to the second storage device via the second network and to transmit via the second communications network a message indicative of the second image data having been written to the second storage device and to read the first image data from the first storage device via the first network, and to generate first drive instructions corresponding to the written first image data;

a second print driver server interconnected to the second network, and configured to read the second image data from the second storage device via the second network and to generate second drive instructions corresponding to the written second image data;

a first image maker configured to generate a representation of the first image in accordance with the first drive instructions; and

a second image maker configured to generate a representation of the second image in accordance with the second drive instructions.

2. Cancelled.

3. (Original) A system according to claim 1, wherein:

the first image maker is a first imagesetter; and

the second image maker is a second imagesetter, different than the first imagesetter.

4. Cancelled.

5. Cancelled.

6. (Original) A system according to claim 1, wherein:

the first communications network includes a respective dedicated link, having a first bandwidth, between the first image processor and the first storage device, and between the first print driver and the first storage device;

the second communications network includes links having a second bandwidth; and the first bandwidth is greater than the second bandwidth.

7. (Original) A system according to claim 1, wherein:

the first image processor is further configured to compress the first image data;

the written first image data is the compressed first image data;

the first print driver is further configured to decompress the written first image data, to compress the generated second image data, and to process the decompressed first image data to generate the first drive instructions; and

the written second image data is the compressed second image data.

8. (Original) A system according to claim 1, wherein:

the second image processor is further configured to generate the second image data in a first format;

the first print driver is further configured to reformat the second image data from the first format to a second format and to compress reformatted second image data; and

the written second image data is the compressed reformatted second image data.

9. (Original) A system according to claim 1, wherein:

the first print driver is further configured to compress the second image data; and the written second image data is the compressed second image data.

10. (Original) A system according to claim 1, wherein:

the written second image data is in a first format;

the first print driver is further configured to reformat the written second image data from the first format to a second format; and

the second print driver is further configured to process the reformatted second image data to generate the second drive instructions.

11. (Original) A system according to claim 1, wherein:

the first image processor is further configured to convert a first sequence of characters representing the first image into a second sequence of characters, including a predefined compression code for one of white image data and black image data, in order to generate the first image data;

the written first image data includes the second sequence of characters; and

the first print driver is further configured to covert the written second sequence of characters into the first sequence of characters based on the predefined compression code in order to generate the first drive instructions.

12. (Original) A system according to claim 11, wherein:

the first image processor is further configured to covert the first sequence of characters by reading a first character in the first sequence of characters, to determine if the read first character represents the one of the white and the black image data, if so, to read one or more characters occurring immediately subsequent to the first character in the first sequence of characters, to determine if the read one or more characters match the read first character, and, if so, to generate the second sequence of characters to represent the matching one or more characters.

13. (Currently amended) A method for generating a representation of an image, comprising:

- writing, by a first raster image processor, first image data, representing a first image, to a first storage device via a first communications network;
- transmitting, by the first raster image processor, via a second communications network, a message indicative of the first image data having been written to the first storage device;
- receiving by a first print driver server the message indicative of the first image data having been written to the first storage device;
- retrieving by the first print driver server the written first image data from the first storage device via the first communications network;
- generating by the first print driver server first instructions corresponding to the retrieved first image data;
- writing by a second raster image processor second image data, representing a second image, to a second storage device via the second communications network;
- retrieving by a second print driver server the written second image data from the second storage device;
- ~~transmitting the retrieved second image data via a second communications network;~~
- generating second instructions corresponding to the ~~transmitted~~ retrieved second image data;
- generating by a first image maker a representation of the first image in accordance with the first instructions; and
- generating by a second image maker a representation of the second image in accordance with the second instructions.

14. Cancelled.

15. (Original) A method according to claim 14, wherein the second image data is written to the second storage device via the second communications network.

16. Cancelled.

17. (Original) A method according to claim 13, wherein:

the first communications network has an associated first bandwidth;
the second communications network has an associated second bandwidth; and
the first bandwidth is greater than the second bandwidth.

18. (Original) A method according to claim 13, further comprising:

compressing the first image data, wherein the written first image data is the compressed first image data and the retrieved first image data is the written compressed first image data;
decompressing the retrieved first image data; and
processing the decompressed first image data to generate the first drive instructions.

19. (Original) A method according to claim 13, further comprising:

reformatting the second image data from a first format to a second format; and
compressing the reformatted second image data;
wherein the written second image data and the retrieved written second image data are the compressed reformatted second image data.

20. (Original) A method according to claim 13, further comprising:

compressing the second image data;
wherein the written second image data and the retrieved written second image data are the compressed second image data.

21. (Original) A method according to claim 13, further comprising:

reformatting the written second image data from a first format to a second format,
wherein the transmitted second image data is the reformatted second image data; and
processing the reformatted second image data to generate the second drive instructions.

22. (Original) A method according to claim 13, further comprising:

generating the first image data by converting a first sequence of characters representing the first image into a second sequence of characters, including a predefined compression code for one of white image data and black image data, wherein the written first image data includes the second sequence of characters; and

converting the written second sequence of characters into the first sequence of characters based on the predefined compression code in order to generate the first drive instructions.

23. (Original) A method according to claim 22, wherein:

the first sequence of characters are converted by reading a first character in the first sequence of characters, determining if the read first character represents the one of the white and the black image data, if so, reading one or more characters occurring immediately subsequent to the first character in the first sequence of characters, determining if the read one or more characters match the read first character, and, if so, generating the second sequence of characters to represent the matching one or more characters.

24. (New) The method of claim 1, wherein the message indicative of the first image data having been written to the first storage device identifies the location of the first image data on the first storage device.

25. (New) The method of claim 1, wherein the message indicative of the second image data having been written to the second storage device identifies the location of the second image data on the second storage device.